

INTERLUBE

Leaders in Lubrication Solutions



Interlube Single Point Lubricators

PS-01



PC-01



PF-01



Interlube - providers of the ultimate in lubrication solutions...

Interlube Single Point Lubricators

Easy Lubrication - the Single Point Solutions

Interlube's easy to fit range of single point automatic lubricators are safe, reliable, operating fully independently in any position - even under water. Since 1922 Interlube has been a leader in lubrication technology, design, and production. Working in partnership with our valued customers, distributors and fitting agents Interlube continues to provide quality products and excellent service.



PS-01

PS-01 *The precision lubricator economically supplying precise applications of lubricant.*

- operates fully automatic, temperature independent and precise
- electromechanical drive with exchangeable battery set
- 4 discharge periods (1,3,6, 12 months) - individually adjustable*
- application temperature ranging from -10C / 14 F to +50C / 122 F
- LC-unit 120 cm³ (Lubrication canister) replaceable on site
- L165mm ø 63,5mm/screwed joint ø 71mm weight with SFO1 approx. 500g



PC-01

PC-01 *The classic choice for e.g. single point lubrication of roller and sliding bearings, chains, open gears & sliding guideways.*

- operates in any position, even under water.
- builds up pressure up to 4 bar max.
- 120cm³ of lubricant
- activating screws in various colours for different discharge periods:*
1 month (yellow), 3 months (green), 6 months (red).
- L99mm - ø 59mm/cap ring ø 70mm - weight with SFO1 approx. 260g



PF-01

PF-01 *The low temperature lubricator ensures reliability in frosty climates.*

- electrochemical drive
- builds up pressure up to 4 bar max.
- liquid electrolyte: environmentally safe acetic acid.
- end of lubrication period visible
- application temperature from -25C/-13F bis + 10C/50 F
- black activating screw
- 9mm ø 59mm/cap ring ø 70mm - weight with SFO1 approx. 260g



Interlube Systems Ltd

St Modwen Road, Plymouth,

Devon, England PL6 8LH

Tel: +44 (0)1752.676000

Fax: +44 (0)1752 676001